

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
29 April 2004 (29.04.2004)

PCT

(10) International Publication Number
WO 2004/035454 A1

(51) International Patent Classification⁷: **B66C 13/14**

(74) Agent: MURGITROYD & COMPANY; 165-169 Scotland Street, Glasgow G5 8PL (GB).

(21) International Application Number:
PCT/GB2003/004317

(22) International Filing Date: 7 October 2003 (07.10.2003)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
0223964.8 15 October 2002 (15.10.2002) GB

(71) Applicant (for all designated States except US): DEEP
TEK LIMITED [GB/GB]; Kilburns House, Newport-on-
Tay, Fife DD6 8PL (GB).

(72) Inventor; and


(75) Inventor/Applicant (for US only): CRAWFORD,
Alexander, Charles [GB/GB]; Kilburns Farm, New-
port-on-Tay, Fife DD6 8PL (GB).

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

[Continued on next page]

(54) Title: APPARATUS AND A METHOD FOR USE IN HANDLING A LOAD



(57) Abstract: Apparatus for use in handling a load where a load-bearing rope (1) and a service cable (2) are inter-wound as they are being paid out, having a wrapping device for wrapping a securing member (17) around the service cable and the load-bearing rope, and to unwrap the securing member from the service cable and load-bearing rope as either of them is recovered. The securing member is wound around the service cable and the hoist rope, to hold the service cable relative to the load-bearing rope and to reduce the extent of creeping of the service cable down the load-bearing rope. The securing member can be planar, in the form of a strip, tape or ribbon, or can have a circular cross-section, in the form of a rope. In preferred embodiments, the securing member is resilient and is applied to the rope in tension.

WO 2004/035454 A1

WO 2004/035454 A1



Published:

— with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.